



Sales Director: Darcy
Whatsapp: 008613425174299
Email: Darcy@szledworld.com

Rental indoor led display (640x640cabinet)



Features:

- Seamless connecting tech, high resolution, Presenting the most real pictures
- High contrast,ideal gray scale,presenting The clear and bright pictures
- The appearance is very elegant, quality is Very stable
- Easy to install: No tool needed during Installation
- Light weight:about 7.5kg/cabinet



Application:

Item Name	P5 full color indoor led display	P10 full color indoor led display
Pitch size	5mm	10mm
Module size	320mm*160mm	320mm*160mm
Module pixel(dots)	64dots*32dots	32dots*16dots
Pixel configuration	1R1G1B	1R1G1B
Package mode	SMD3528	SMD3528
Color scale	65536degree/16777216colors	65536degree/16777216colors
Pixel density	40000pixels/square meter	10000pixels/square meter
View angle(H/V)	≥ 120/120degree	≥ 120/120degree
Brightness	≥ 1500cd/m2	≥ 800cd/square meter
Brightness adjustment	64 level automatic or manual	64 level automatic or manual
View distance	3--100m	3--100m
Power consumption	100-1600W/square meter	100-1600W/square meter
Net weight	less than 45kg/square meter	less than 45kg/square meter
Operating temperature	_ 25° C~+60° C	_ 25° C~+60° C
Operating humidity	10%_ 95%RH	10%_ 95%RH
Life time	≥ 100, 000hours	≥ 100, 000hours
Out of control dot	≤ 1/10, 000	≤ 1/10, 000
Whole Display Flatness	≤ 1mm Juncture	≤ 1mm Juncture
Exchange frame speed	> 150frames per second	> 150frames per second
Refresh frame frequency	1920Hz	1920Hz
Power	110V/220V± 15% 50Hz	110V/220V± 15% 50Hz
Operating system	Windows98/Me/2000/Xp	Windows98/Me/2000/Xp
Drive mode	constant current driving, 1/16 or 1/8 scan	constant current driving, 1/8 scan
Display mode	VGA640X480_ VGA1600X1024	VGA640X480_ VGA1600X1024
Protections for outdoor display	IP43	IP43
Maintenance way	Rear access	Rear access
Accepting signal	PAL/NTSC/SECAM, S-Video; VGA; RGB; Composite Video; SDI	PAL/NTSC/SECAM, S-Video; VGA; RGB; Composite Video; SDI
Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to Led World.		